

Garant
Boring bar, steel, left-hand, Shank Ø / insert size: 40/16 mm

Order data

| | |
|--------------|---------------|
| Order number | 251721 40/16 |
| GTIN | 4045197867193 |
| Item class | 21T |

Description

Boring bar, steel 40/16 mm Shank Ø D_s: 40 mm
 ISO code toolholder: A40T MVPNR/L 16
 Setting angle κ: 117.5 degrees
 suitable indexable insert: VN.. 1604..
 Minimum pre-drill Ø D_{min}: 50 mm
 Centre offset L₃: 27 mm

Technical description

| | |
|--------------------------------------|-----------------|
| Shim screw | 259025 3 |
| Minimum pre-drill Ø D _{min} | 50 mm |
| Overall length L | 300 mm |
| Shim | 259031 39 |
| Setting angle κ | 117.5 degrees |
| suitable indexable insert | VN.. 1604.. |
| Clamping claw | 259038 2 |
| Screw for clamp | 259021 1 |
| ISO code toolholder | A40T MVPNR/L 16 |
| Clamping height L ₂ | 38.5 mm |
| Insert size | 16 mm |
| Centre offset L ₃ | 27 mm |

| | |
|-------------------------|------------|
| Shank $\varnothing D_s$ | 40 mm |
| Application type | left-hand |
| Boring depth up to | 3xD |
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Screw for clamping claw | 259180 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8 | 674248 TX8 |
| Shim screw Type 3 | 259025 3 |
| Shim Type 39 | 259031 39 |
| Clamping claw Type 2 | 259038 2 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Clamping claw | 259320 |
| Shim | 259310 |
| Screw for clamping claw Type 1 | 259021 1 |
| Shim screw | 259170 |