

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 40/16 mm

Order data

Order number	251724 40/16
GTIN	4045197868213
Item class	21T

Description

Boring bar, steel 40/16 mm Shank \varnothing D_s : 40 mm
 ISO code toolholder: A40T MVUNR/L 16
 Setting angle κ : 93 degrees
 suitable indexable insert: VN.. 1604..
 Minimum pre-drill \varnothing D_{min} : 50 mm
 Centre offset L_3 : 27 mm

Technical description

Minimum pre-drill \varnothing D_{min}	50 mm
Screw for clamp	259021 1
Clamping height L_2	38.5 mm
Setting angle κ	93 degrees
Overall length L	300 mm
suitable indexable insert	VN.. 1604..
ISO code toolholder	A40T MVUNR/L 16
Clamping claw	259038 4
Shim	259031 39
Shim screw	259025 3
Insert size	16 mm
Centre offset L_3	27 mm

Shank $\varnothing D_s$	40 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Shim	259310
Screw for clamping claw Type 1	259021 1
Clamping claw Type 4	259038 4
Clamp	259322
Screw for clamping claw	259180
Shim screw Type 3	259025 3
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim Type 39	259031 39
Shim screw	259170
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8