

**Garant**
**Boring bar, steel, left-hand, Shank Ø / insert size: 40/16 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 251725 40/16  |
| GTIN         | 4045197868244 |
| Item class   | 21T           |

**Description**

Boring bar, steel 40/16 mm Shank Ø D<sub>s</sub>: 40 mm  
 ISO code toolholder: A40T MVUNR/L 16  
 Setting angle κ: 93 degrees  
 suitable indexable insert: VN.. 1604..  
 Minimum pre-drill Ø D<sub>min</sub>: 50 mm  
 Centre offset L<sub>3</sub>: 27 mm

**Technical description**

|                                      |                 |
|--------------------------------------|-----------------|
| Shim screw                           | 259025 3        |
| Overall length L                     | 300 mm          |
| Screw for clamp                      | 259021 1        |
| Centre offset L <sub>3</sub>         | 27 mm           |
| Minimum pre-drill Ø D <sub>min</sub> | 50 mm           |
| Insert size                          | 16 mm           |
| Setting angle κ                      | 93 degrees      |
| Clamping height L <sub>2</sub>       | 38.5 mm         |
| Clamping claw                        | 259038 4        |
| Shim                                 | 259031 39       |
| suitable indexable insert            | VN.. 1604..     |
| ISO code toolholder                  | A40T MVUNR/L 16 |

|                        |            |
|------------------------|------------|
| Shank Ø D <sub>s</sub> | 40 mm      |
| Application type       | left-hand  |
| Boring depth up to     | 3×D        |
| Standard               | DIN 8024   |
| Through-coolant        | yes        |
| Type of product        | Boring bar |

## Accessories

|  |            |
|--|------------|
| Shim Type 39   | 259031 39  |
| Clamping claw Type 4   | 259038 4   |
| Shim   | 259310     |
| Shim screw Type 3  | 259025 3   |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8                                | 674248 TX8 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Screw for clamping claw  | 259180     |
| Clamp  | 259322     |
| Screw for clamping claw Type 1   | 259021 1   |
| Shim screw   | 259170     |