

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 40/16 mm

Order data

Order number	251728 40/16
GTIN	4045197868268
Item class	21T

Description

Boring bar, steel 40/16 mm Shank \varnothing D_s: 40 mm
 ISO code toolholder: A40T MVZNR/L 16
 Setting angle κ : 95 degrees
 suitable indexable insert: VN.. 1604..
 Minimum pre-drill \varnothing D_{min}: 57 mm
 Centre offset L₃: 35 mm

Technical description

Centre offset L ₃	35 mm
Clamping height L ₂	38.5 mm
Screw for clamp	259021 4
ISO code toolholder	A40T MVZNR/L 16
Clamping claw	259038 2
Overall length L	300 mm
Setting angle κ	95 degrees
Shim screw	259025 3
Shim	259031 39
Minimum pre-drill \varnothing D _{min}	57 mm
Insert size	16 mm
suitable indexable insert	VN.. 1604..

Usable depth T	15 mm
Shank $\varnothing D_s$	40 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Shim screw	259170
Shim	259310
Screw for clamp	259184
Clamping claw	259320
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Screw for clamping claw Type 4	259021 4
Clamping claw Type 2	259038 2
Shim Type 39	259031 39
Shim screw Type 3	259025 3