

**Garant**
**Boring bar, steel, left-hand, Shank Ø / insert size: 40/16 mm**

**Order data**

Order number	251729 40/16
GTIN	4045197868282
Item class	21T

**Description**

Boring bar, steel 40/16 mm Shank Ø D<sub>s</sub>: 40 mm

ISO code toolholder: A40T MVZNR/L 16

Setting angle κ: 95 degrees

suitable indexable insert: VN.. 1604..

Minimum pre-drill Ø D<sub>min</sub>: 57 mm

Centre offset L<sub>3</sub>: 35 mm

**Technical description**

Setting angle κ	95 degrees
ISO code toolholder	A40T MVZNR/L 16
Minimum pre-drill Ø D <sub>min</sub>	57 mm
Insert size	16 mm
Shim screw	259025 3
Screw for clamp	259021 4
Shim	259031 39
Overall length L	300 mm
Clamping height L <sub>2</sub>	38.5 mm
Centre offset L <sub>3</sub>	35 mm
Clamping claw	259038 2
suitable indexable insert	VN.. 1604..

Usable depth T	15 mm
Shank $\varnothing D_s$	40 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Shim screw	259170
Clamping claw	259320
Shim	259310
Screw for clamp	259184
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim Type 39	259031 39
Shim screw Type 3	259025 3
Clamping claw Type 2	259038 2
Screw for clamping claw Type 4	259021 4