

**Garant**
**eco clamping toolholder, right-hand, Shank / insert size: 20/08 mm**

**Order data**

Order number	251900 20/08
GTIN	4045197809025
Item class	21U

**Description**
**Version:**

With internal coolant feed right to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and increased process reliability.

With flank face cooling.

**Note:**

Coolant transfer only possible in conjunction with GARANT eco system toolholders No. 319001 – 319886 or for shank length < 125 mm plus No. 317900.

Through-coolant: yes

ISO code toolholder: DWLNR/L 2020K08

suitable indexable insert: WN.. 0804..

Functional width  $L_4$ : 25 mm

Head length  $L_1$ : 32 mm

Overall length L: 125 mm

Shim: 259033 6

**Technical description**

ISO code toolholder	DWLNR/L 2020K08
suitable indexable insert	WN.. 0804..
Overall length L	125 mm
Functional width $L_4$	25 mm
Clamp, screw, spring	259036 10

Insert size	8 mm
Head length L <sub>1</sub>	32 mm
Shim screw	259027 4
Shim	259033 6
Shank size	20 mm
Application type	right-hand
Standard	DIN ISO 5610
Through-coolant	yes
Setting angle κ	95 degrees
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
--	------------