

Garant
eco clamping toolholder, left-hand, Shank / insert size: 20/08 mm

Order data

Order number	251901 20/08
GTIN	4045197809056
Item class	21U

Description
Version:

With internal coolant feed right to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and increased process reliability.

With flank face cooling.

Note:

Coolant transfer only possible in conjunction with GARANT eco system toolholders No. 319001 – 319886 or for shank length < 125 mm plus No. 317900.

Through-coolant: yes

ISO code toolholder: DWLNR/L 2020K08

suitable indexable insert: WN.. 0804..

Functional width L_4 : 25 mm

Head length L_1 : 32 mm

Overall length L: 125 mm

Shim: 259033 6

Technical description

suitable indexable insert	WN.. 0804..
Shim	259033 6
Shim screw	259027 4
Clamp, screw, spring	259036 9
ISO code toolholder	DWLNR/L 2020K08

Insert size	8 mm
Functional width L_4	25 mm
Overall length L	125 mm
Shank size	20 mm
Head length L_1	32 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	yes
Setting angle κ	95 degrees
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10