

## Garant

### QuickTurn clamping toolholder, right-hand, Shank / insert size: 25/08 mm



#### Order data

Order number	251906 25/08
GTIN	4045197651228
Item class	21U

#### Description

##### Advantage:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

##### Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Through-coolant: no

ISO code toolholder: DWLNR/L 2525M08

suitable indexable insert: WN.. 0804..

Functional width  $L_4$ : 32 mm

Head length  $L_1$ : 32 mm

Overall length L: 150 mm

Shim: 259031 42

#### Technical description

suitable indexable insert	WN.. 0804..
Shank size	25 mm
Head length $L_1$	32 mm

Shim screw	259025 4
Cutting point / joint	25×25 mm
Shim	259031 42
ISO code toolholder	DWLNRL 2525M08
Clamp	259038 9
Insert size	8 mm
Functional width L <sub>4</sub>	32 mm
Overall length L	150 mm
Application type	right-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	95 degrees
Type of product	Boring bar

## Accessories

Shim screw	259171
Clamping claw	259353
Shim	259581
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim screw Type 4	259025 4
Shim Type 42	259031 42
Clamping claw Type 9	259038 9