

Garant
QuickTurn clamping toolholder, left-hand, Shank / insert size: 25/08 mm

Order data

Order number	251907 25/08
GTIN	4045197558299
Item class	21U

Description
Advantage:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Application:

Inserts can be changed without using tools. **Release the stop at the push of a button – change the insert – press the clamp to secure it.**

A simple and convenient way to reduce non-productive times.

Consistent clamping force, high interchange accuracy, maintenance-free.

Through-coolant: no

ISO code toolholder: DWLNR/L 2525M08

suitable indexable insert: WN.. 0804..

Functional width L₄: 32 mm

Head length L₁: 32 mm

Overall length L: 150 mm

Shim: 259031 42

Technical description

Cutting point / joint	25×25 mm
Clamp	259038 10
Shim screw	259025 4

suitable indexable insert	WN.. 0804..
Shim	259031 42
Functional width L ₄	32 mm
Insert size	8 mm
Shank size	25 mm
Head length L ₁	32 mm
ISO code toolholder	DWLNR/L 2525M08
Overall length L	150 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	no
Setting angle κ	95 degrees
Type of product	Boring bar

Accessories

Shim screw	259171
Clamping claw	259354
Shim	259581
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim Type 42	259031 42
Shim screw Type 4	259025 4
Clamping claw Type 10	259038 10