

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 25/08 mm

Order data

Order number	251936 25/08
GTIN	4045197651419
Item class	21T

Description

Boring bar, steel 25/08 mm Shank \varnothing D_s: 25 mm
 ISO code toolholder: A25R MWLNR/L08
 Setting angle κ : 95 degrees
 suitable indexable insert: WN.. 0804..
 Minimum pre-drill \varnothing D_{min}: 32 mm
 Centre offset L₃: 17 mm

Technical description

Pin	259049 3
Shim	259031 41
Clamping claw	259038 12
Minimum pre-drill \varnothing D _{min}	32 mm
Centre offset L ₃	17 mm
suitable indexable insert	WN.. 0804..
Insert size	8 mm
ISO code toolholder	A25R MWLNR/L08
Screw set	259023 3
Overall length L	200 mm
Clamping height L ₂	24 mm
Setting angle κ	95 degrees

Shank $\varnothing D_s$	25 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Pin Type 3	259049 3
Shim	259580
Pin	259610
Set of screws 10 pieces	259630
Clamping claw Type 12	259038 12
Shim Type 41	259031 41
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping claw	259560
Set of screws 10 pieces Type 3	259023 3
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15