

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 32/08 mm

Order data

Order number	251936 32/08
GTIN	4045197651426
Item class	21T

Description

Boring bar, steel 32/08 mm Shank \varnothing D_s: 32 mm
 ISO code toolholder: A32S MWLNR/L08
 Setting angle κ : 95 degrees
 suitable indexable insert: WN.. 0804..
 Minimum pre-drill \varnothing D_{min}: 40 mm
 Centre offset L₃: 22 mm

Technical description

Pin	259049 5
ISO code toolholder	A32S MWLNR/L08
Minimum pre-drill \varnothing D _{min}	40 mm
Centre offset L ₃	22 mm
Clamping claw	259038 12
suitable indexable insert	WN.. 0804..
Insert size	8 mm
Shim	259031 41
Screw set	259023 3
Overall length L	250 mm
Clamping height L ₂	31 mm
Setting angle κ	95 degrees

Shank Ø D _s	32 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Pin	259610
Shim	259580
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping claw Type 12	259038 12
Set of screws 10 pieces	259630
Pin Type 5	259049 5
Clamping claw	259560
Shim Type 41	259031 41
Set of screws 10 pieces Type 3	259023 3