

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 40/08 mm

Order data

Order number	251936 40/08
GTIN	4045197651433
Item class	21T

Description

Boring bar, steel 40/08 mm Shank \varnothing D₃: 40 mm
 ISO code toolholder: A40T MWLNR/L08
 Setting angle κ : 95 degrees
 suitable indexable insert: WN.. 0804..
 Minimum pre-drill \varnothing D_{min}: 50 mm
 Centre offset L₃: 27 mm

Technical description

Centre offset L ₃	27 mm
suitable indexable insert	WN.. 0804..
Insert size	8 mm
Minimum pre-drill \varnothing D _{min}	50 mm
Screw set	259023 3
Shim	259031 41
ISO code toolholder	A40T MWLNR/L08
Pin	259049 5
Clamping claw	259038 12
Overall length L	300 mm
Clamping height L ₂	38.5 mm
Setting angle κ	95 degrees

Shank $\varnothing D_s$	40 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Clamping claw Type 12	259038 12
Pin	259610
Set of screws 10 pieces Type 3	259023 3
Shim	259580
Pin Type 5	259049 5
Set of screws 10 pieces	259630
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim Type 41	259031 41
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Clamping claw	259560