

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 25/08 mm**

**Order data**

Order number	251937 25/08
GTIN	4045197651440
Item class	21T

**Description**

Boring bar, steel 25/08 mm Shank  $\varnothing$  D<sub>3</sub>: 25 mm  
 ISO code toolholder: A25R MWLNR/L08  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: WN.. 0804..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 32 mm  
 Centre offset L<sub>3</sub>: 17 mm

**Technical description**

Pin	259049 3
Minimum pre-drill $\varnothing$ D <sub>min</sub>	32 mm
Shim	259031 41
Insert size	8 mm
suitable indexable insert	WN.. 0804..
ISO code toolholder	A25R MWLNR/L08
Clamping claw	259038 12
Screw set	259023 3
Centre offset L <sub>3</sub>	17 mm
Overall length L	200 mm
Clamping height L <sub>2</sub>	24 mm
Setting angle $\kappa$	95 degrees

Shank Ø D <sub>s</sub>	25 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Shim Type 41	259031 41
Clamping claw Type 12	259038 12
Pin	259610
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of screws 10 pieces	259630
Clamping claw	259560
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of screws 10 pieces Type 3	259023 3
Shim	259580
Pin Type 3	259049 3