

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 32/08 mm

Order data

Order number	251937 32/08
GTIN	4045197651457
Item class	21T

Description

Boring bar, steel 32/08 mm Shank \varnothing D₃: 32 mm

ISO code toolholder: A32S MWLNR/L08

Setting angle κ : 95 degrees

suitable indexable insert: WN.. 0804..

Minimum pre-drill \varnothing D_{min}: 40 mm

Centre offset L₃: 22 mm

Technical description

suitable indexable insert	WN.. 0804..
Minimum pre-drill \varnothing D _{min}	40 mm
Insert size	8 mm
Screw set	259023 3
Clamping claw	259038 12
Centre offset L ₃	22 mm
Pin	259049 5
Shim	259031 41
ISO code toolholder	A32S MWLNR/L08
Overall length L	250 mm
Clamping height L ₂	31 mm
Setting angle κ	95 degrees

Shank Ø D _s	32 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Shim Type 41	259031 41
Set of screws 10 pieces	259630
Shim	259580
Pin	259610
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping claw Type 12	259038 12
Clamping claw	259560
Set of screws 10 pieces Type 3	259023 3
Pin Type 5	259049 5
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15