

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 40/08 mm

Order data

Order number	251937 40/08
GTIN	4045197651464
Item class	21T

Description

Boring bar, steel 40/08 mm Shank \varnothing D₃: 40 mm
 ISO code toolholder: A40T MWLNR/L08
 Setting angle κ : 95 degrees
 suitable indexable insert: WN.. 0804..
 Minimum pre-drill \varnothing D_{min}: 50 mm
 Centre offset L₃: 27 mm

Technical description

Centre offset L ₃	27 mm
Pin	259049 5
Screw set	259023 3
Clamping claw	259038 12
Minimum pre-drill \varnothing D _{min}	50 mm
Insert size	8 mm
suitable indexable insert	WN.. 0804..
ISO code toolholder	A40T MWLNR/L08
Shim	259031 41
Overall length L	300 mm
Clamping height L ₂	38.5 mm
Setting angle κ	95 degrees

Shank Ø D _s	40 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Pin Type 5	259049 5
Set of screws 10 pieces Type 3	259023 3
Shim	259580
Clamping claw	259560
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Pin	259610
Clamping claw Type 12	259038 12
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of screws 10 pieces	259630
Shim Type 41	259031 41