

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 16/06 mm

Order data

Order number	251942 16/06
GTIN	4045197651471
Item class	21T

Description

Boring bar, steel 16/06 mm Shank \varnothing D_s : 16 mm
 ISO code toolholder: A16M PWLNR/L06
 Setting angle κ : 95 degrees
 suitable indexable insert: WN.. 0604..
 Minimum pre-drill \varnothing D_{min} : 21 mm
 Centre offset L_3 : 11 mm

Technical description

Insert size	6 mm
Minimum pre-drill \varnothing D_{min}	21 mm
Lever	259015 14
suitable indexable insert	WN.. 0604..
ISO code toolholder	A16M PWLNR/L06
Centre offset L_3	11 mm
Lever screw	259018 10
Overall length L	150 mm
Clamping height L_2	15.25 mm
Setting angle κ	95 degrees
Shank \varnothing D_s	16 mm
Application type	right-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Lever screw Type 10	259018 10
Lever	259075
Lever screw	259140
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Lever Type 14	259015 14
PrecisionBit for hex, shank E 6.3 Hexagon 2 mm	674242 2