

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 20/06 mm

Order data

Order number	251942 20/06
GTIN	4045197651488
Item class	21T

Description

Boring bar, steel 20/06 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: A20Q PWLNR/L06
 Setting angle κ : 95 degrees
 suitable indexable insert: WN.. 0604..
 Minimum pre-drill $\varnothing D_{min}$: 25 mm
 Centre offset L_3 : 13 mm

Technical description

suitable indexable insert	WN.. 0604..
Minimum pre-drill $\varnothing D_{min}$	25 mm
Insert size	6 mm
Centre offset L_3	13 mm
Lever	259015 14
Lever screw	259018 10
ISO code toolholder	A20Q PWLNR/L06
Overall length L	180 mm
Clamping height L_2	19 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	20 mm
Application type	right-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for hex, shank E 6.3 Hexagon 2 mm	674242 2
Lever screw Type 10	259018 10
Lever	259075
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Lever screw	259140
Lever Type 14	259015 14