

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 20/06 mm**

**Order data**

Order number	251943 20/06
GTIN	4045197651501
Item class	21T

**Description**

Boring bar, steel 20/06 mm Shank  $\varnothing D_s$ : 20 mm  
 ISO code toolholder: A20Q PWLNR/L06  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: WN.. 0604..  
 Minimum pre-drill  $\varnothing D_{min}$ : 25 mm  
 Centre offset  $L_3$ : 13 mm

**Technical description**

Centre offset $L_3$	13 mm
Lever	259015 14
Minimum pre-drill $\varnothing D_{min}$	25 mm
Lever screw	259018 10
Insert size	6 mm
suitable indexable insert	WN.. 0604..
ISO code toolholder	A20Q PWLNR/L06
Overall length L	180 mm
Clamping height $L_2$	19 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	20 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Lever Type 14	259015 14
Lever screw	259140
Lever screw Type 10	259018 10
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for hex, shank E 6.3 Hexagon 2 mm	674242 2
Lever	259075