


Garant
CNGA 09T304, BU7220, Cutting edge version: G


Order data

Order number	255403 G
GTIN	4045197895097
Item class	21H

Description

Version:

Fitted with 2 cutters.

Description:

New type of CBN with a balanced combination wear-resistance and tensile strength for general-purpose use in hardened steel up to 67 HRC in combination with a special constitution. For use both in continuous cutting and also in slightly interrupted and heavily interrupted cutting.

Corner radius: 0.4 mm

Grade: BU7220

Cutting depth a_p : 0.05 - 0.2 mm

Feed f : 0.05 - 0.15 mm/rev.

Cutting speed v_c main application: 90 - 140 m/min

Cutting edge version: G

Technical description

Cutting edge version	G
Corner radius	0.4 mm
Tool material	CBN

Grade	BU7220
Cutting conditions	heavily interrupted
Cutting conditions	continuous
Cutting conditions	slightly interrupted
Cutting speed v_c main application	90 - 140 m/min
Feed f	0.05 - 0.15 mm/rev.
Finishing/roughing assignment	Finishing
Cutting depth a_p	0.05 - 0.2 mm
ISO code indexable insert	CNGA 09T304
Number of changes/inserts	2
Product name attribute	BU7220
Type of product	Indexable insert for turning