

**Garant**
**WNGA 060408, BU7220, Cutting edge version: G**


## Order data

Order number	255472 G
GTIN	4045197895462
Item class	21H

## Description

### Version:

Fitted with 3 cutters.

### Description:

New type of CBN with a balanced combination wear-resistance and tensile strength for general-purpose use in hardened steel up to 67 HRC in combination with a special constitution. For use both in continuous cutting and also in slightly interrupted and heavily interrupted cutting.

Grade: BU7220

Cutting edge version: G

Cutting depth  $a_p$ : 0.05 - 0.2 mm

Feed  $f$ : 0.05 - 0.15 mm/rev.

Cutting speed  $v_c$  main application: 90 - 140 m/min

## Technical description

Grade	BU7220
Cutting edge version	G
Corner radius	0.8 mm

Cutting speed $v_c$ main application	90 - 140 m/min
Feed $f$	0.05 - 0.15 mm/rev.
Cutting conditions	heavily interrupted
Cutting conditions	slightly interrupted
Cutting conditions	continuous
Finishing/roughing assignment	Finishing
Tool material	CBN
Cutting depth $a_p$	0.05 - 0.2 mm
ISO code indexable insert	WNGA 060408
Number of changes/inserts	3
Product name attribute	BU7220
Type of product	Indexable insert for turning