

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 12/06 mm

Order data

Order number	260016 12/06
GTIN	4045197651822
Item class	21T

Description

Boring bar carbide 12/06 mm Shank $\varnothing D_s$: 12 mm

ISO code toolholder: E12M SCLCR/L06

Setting angle κ : 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill $\varnothing D_{\min}$: 14 mm

Centre offset L_3 : 8 mm

Technical description

Pack of insert screws	269028 7
Insert size	6 mm
suitable indexable insert	CC.. 0602..
Centre offset L_3	8 mm
ISO code toolholder	E12M SCLCR/L06
Minimum pre-drill $\varnothing D_{\min}$	14 mm
Head length L_1	10 mm
Overall length L	150 mm
Clamping height L_2	11.5 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	12 mm
Application type	right-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500