

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 20/09 mm

Order data

Order number	260016 20/09
GTIN	4045197651846
Item class	21T

Description

Boring bar carbide 20/09 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: E20S SCLCR/L09
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 09T3..
 Minimum pre-drill $\varnothing D_{min}$: 23 mm
 Centre offset L_3 : 12 mm

Technical description

suitable indexable insert	CC.. 09T3..
Centre offset L_3	12 mm
Insert size	9 mm
Minimum pre-drill $\varnothing D_{min}$	23 mm
ISO code toolholder	E20S SCLCR/L09
Head length L_1	16 mm
Pack of insert screws	269028 8
Overall length L	250 mm
Clamping height L_2	19 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	20 mm
Application type	right-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269414
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15