

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 4/03 mm

Order data

Order number	260016 4/03
GTIN	4045197651778
Item class	21T

Description

Boring bar carbide 4/03 mm Shank $\varnothing D_s$: 4 mm
 ISO code toolholder: E04G SCLCR/L03
 Cutting point / joint: 4 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0301..
 Minimum pre-drill $\varnothing D_{\min}$: 5 mm

Technical description

Insert size	3 mm
ISO code toolholder	E04G SCLCR/L03
suitable indexable insert	CC.. 0301..
Minimum pre-drill $\varnothing D_{\min}$	5 mm
Pack of insert screws	269028 13
Centre offset L_3	2.5 mm
Cutting point / joint	4 mm
Head length L_1	10 mm
Overhang L_1	15 mm
Overall length L	90 mm
Clamping height L_2	3.8 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	4 mm

Application type	right-hand
Boring depth up to	8xD
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269412
Set of insert screws 10 pieces	269419
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 13	269028 13
Set of insert screws Type 6	269028 6