

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 10/06 mm

Order data

Order number	260017 10/06
GTIN	4045197651891
Item class	21T

Description

Boring bar carbide 10/06 mm Shank $\varnothing D_s$: 10 mm
 ISO code toolholder: E10K SCLCR/L06
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill $\varnothing D_{min}$: 12 mm
 Centre offset L_3 : 6 mm

Technical description

Centre offset L_3	6 mm
suitable indexable insert	CC.. 0602..
Insert size	6 mm
Head length L_1	10 mm
ISO code toolholder	E10K SCLCR/L06
Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	12 mm
Overall length L	125 mm
Clamping height L_2	9.6 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500