

**Garant**
**Boring bar carbide, left-hand, Shank  $\varnothing$  / insert size: 12/06 mm**

**Order data**

Order number	260017 12/06
GTIN	4045197651907
Item class	21T

**Description**

Boring bar carbide 12/06 mm Shank  $\varnothing D_s$ : 12 mm

ISO code toolholder: E12M SCLCR/L06

Setting angle  $\kappa$ : 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill  $\varnothing D_{min}$ : 14 mm

Centre offset  $L_3$ : 8 mm

**Technical description**

Centre offset $L_3$	8 mm
Insert size	6 mm
Minimum pre-drill $\varnothing D_{min}$	14 mm
Pack of insert screws	269028 7
suitable indexable insert	CC.. 0602..
Head length $L_1$	10 mm
ISO code toolholder	E12M SCLCR/L06
Overall length L	150 mm
Clamping height $L_2$	11.5 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	12 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7