

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 4/03 mm

Order data

Order number	260017 4/03
GTIN	4045197651853
Item class	21T

Description

Boring bar carbide 4/03 mm Shank $\varnothing D_s$: 4 mm

ISO code toolholder: E04G SCLCR/L03

Setting angle κ : 95 degrees

suitable indexable insert: CC.. 0301..

Minimum pre-drill $\varnothing D_{min}$: 5 mm

Centre offset L_3 : 2.5 mm

Technical description

suitable indexable insert	CC.. 0301..
Head length L_1	10 mm
Centre offset L_3	2.5 mm
Minimum pre-drill $\varnothing D_{min}$	5 mm
Pack of insert screws	269028 13
ISO code toolholder	E04G SCLCR/L03
Insert size	3 mm
Overall length L	90 mm
Clamping height L_2	3.8 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	4 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Set of insert screws 10 pieces	269419
Set of insert screws 10 pieces	269412
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 6	269028 6
Set of insert screws Type 13	269028 13