

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 5/03 mm

Order data

Order number	260017 5/03
GTIN	4045197651860
Item class	21T

Description

Boring bar carbide 5/03 mm Shank $\varnothing D_s$: 5 mm

ISO code toolholder: E05H SCLCR/L03

Setting angle κ : 95 degrees

suitable indexable insert: CC.. 0301..

Minimum pre-drill $\varnothing D_{\min}$: 6 mm

Centre offset L_3 : 3 mm

Technical description

suitable indexable insert	CC.. 0301..
Minimum pre-drill $\varnothing D_{\min}$	6 mm
ISO code toolholder	E05H SCLCR/L03
Centre offset L_3	3 mm
Head length L_1	10 mm
Insert size	3 mm
Pack of insert screws	269028 19
Overall length L	100 mm
Clamping height L_2	4.8 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	5 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Pack of insert screws 10 pieces	269429
Set of insert screws Type 19	269028 19
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500