

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 6/03 mm

Order data

Order number	260017 6/03
GTIN	4045197651877
Item class	21T

Description

Boring bar carbide 6/03 mm Shank $\varnothing D_s$: 6 mm
 ISO code toolholder: E06J SCLCR/L03
 Cutting point / joint: 6 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0301..
 Minimum pre-drill $\varnothing D_{min}$: 7 mm

Technical description

Minimum pre-drill $\varnothing D_{min}$	7 mm
suitable indexable insert	CC.. 0301..
Centre offset L_3	3.5 mm
Head length L_1	10 mm
Insert size	3 mm
Pack of insert screws	269028 19
ISO code toolholder	E06J SCLCR/L03
Cutting point / joint	6 mm
Overhang L_1	45 mm
Overall length L	110 mm
Clamping height L_2	5.8 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	6 mm

Application type	left-hand
Boring depth up to	8×D
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Pack of insert screws 10 pieces	269429
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 19	269028 19