

eco screw-on toolholder, left-hand, Shank size / insert size: 20/09 mm



Order data

Order number	260021 20/09
GTIN	4045197945181
Item class	21U

Description

Version:

With internal coolant feed right to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and increased process reliability. With flank face cooling.

Note

Coolant transfer only in conjunction with GARANT eco-system toolholders No. 317900 – 319886.

Through-coolant: yes

ISO code toolholder: SCLCR/L 2020X09 suitable indexable insert: CC.. 09T3..

Functional width L₄: 25 mm Head length L₁: 27 mm Overall length L: 86 mm

Pack of insert screws: 269028 28

Technical description

suitable indexable insert	CC., 09T3.,
CHITANIA INGAVANIA INCART	(((1)) ()
SUITADIE IIIUEVADIE IIISELL	CC., 0913.,



Head length L₁	27 mm
Overall length L	86 mm
Functional width L ₄	25 mm
Pack of insert screws	269028 28
Insert size	9 mm
ISO code toolholder	SCLCR/L 2020X09
Shank size	20 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	yes
Setting angle κ	95 degrees
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15