

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 0610/03 mm

Order data

| | |
|--------------|----------------|
| Order number | 260022 0610/03 |
| GTIN | 4045197651976 |
| Item class | 21T |

Description

Boring bar HSS 0610/03 mm Shank $\varnothing D_s$: 10 mm
 ISO code toolholder: AH0610H SCLCR/L03
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0301..
 Minimum pre-drill $\varnothing D_{min}$: 7 mm
 Centre offset L_3 : 2.5 mm

Technical description

| | |
|---|-------------------|
| Minimum pre-drill $\varnothing D_{min}$ | 7 mm |
| Head length L_1 | 24 mm |
| Centre offset L_3 | 2.5 mm |
| Pack of insert screws | 269028 13 |
| Insert size | 3 mm |
| suitable indexable insert | CC.. 0301.. |
| Neck width L_4 | 6 mm |
| ISO code toolholder | AH0610H SCLCR/L03 |
| Overall length L | 100 mm |
| Clamping height L_2 | 9 mm |
| Setting angle κ | 95 degrees |
| Shank $\varnothing D_s$ | 10 mm |

| | |
|--------------------|------------|
| Application type | right-hand |
| Boring depth up to | 5×D |
| Tool material | HSS |
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Set of insert screws 10 pieces | 269419 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6 | 674248 TX6 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Set of insert screws Type 13 | 269028 13 |