

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 08/06 mm

Order data

| | |
|--------------|---------------|
| Order number | 260022 08/06 |
| GTIN | 4045197651990 |
| Item class | 21T |

Description

Boring bar HSS 08/06 mm Shank $\varnothing D_s$: 8 mm
 ISO code toolholder: AH08K SCLCR/L06
 Cutting point / joint: 8 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill $\varnothing D_{min}$: 10 mm

Technical description

| | |
|---|-----------------|
| suitable indexable insert | CC.. 0602.. |
| Pack of insert screws | 269028 7 |
| Centre offset L_3 | 5 mm |
| Minimum pre-drill $\varnothing D_{min}$ | 10 mm |
| ISO code toolholder | AH08K SCLCR/L06 |
| Cutting point / joint | 8 mm |
| Insert size | 6 mm |
| Overall length L | 125 mm |
| Clamping height L_2 | 7 mm |
| Setting angle κ | 95 degrees |
| Shank $\varnothing D_s$ | 8 mm |
| Application type | right-hand |

| | |
|--------------------|------------|
| Boring depth up to | 5×D |
| Tool material | HSS |
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Set of insert screws 10 pieces | 269413 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8 | 674248 TX8 |
| Set of insert screws Type 7 | 269028 7 |