

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 0810/06 mm

Order data

Order number	260022 0810/06
GTIN	4045197652003
Item class	21T

Description

Boring bar HSS 0810/06 mm Shank \varnothing D₃: 10 mm
 ISO code toolholder: AH0810J SCLCR/L06
 Cutting point / joint: 10 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill \varnothing D_{min}: 12 mm

Technical description

Cutting point / joint	10 mm
suitable indexable insert	CC.. 0602..
Centre offset L ₃	6 mm
Neck width	8 mm
Minimum pre-drill \varnothing D _{min}	12 mm
ISO code toolholder	AH0810J SCLCR/L06
Pack of insert screws	269028 7
Overhang L ₁ recessed holders	32 mm
Insert size	6 mm
Overall length L	110 mm
Clamping height L ₂	9 mm
Setting angle κ	95 degrees

Shank $\varnothing D_s$	10 mm
Application type	right-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set HSS	260024