

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 10/06 mm

Order data

Order number	260022 10/06
GTIN	4045197652010
Item class	21T

Description

Boring bar HSS 10/06 mm Shank \varnothing D_s : 10 mm
 ISO code toolholder: AH10K SCLCR/L06
 Cutting point / joint: 10 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill \varnothing D_{min} : 12 mm

Technical description

Insert size	6 mm
suitable indexable insert	CC.. 0602..
Cutting point / joint	10 mm
Minimum pre-drill \varnothing D_{min}	12 mm
Pack of insert screws	269028 7
Centre offset L_3	6 mm
ISO code toolholder	AH10K SCLCR/L06
Overall length L	125 mm
Clamping height L_2	9 mm
Setting angle κ	95 degrees
Shank \varnothing D_s	10 mm
Application type	right-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7