

**Garant**
**Boring bar HSS, right-hand, Shank  $\varnothing$  / insert size: 1012/06 mm**

**Order data**

Order number	260022 1012/06
GTIN	4045197652027
Item class	21T

**Description**

Boring bar HSS 1012/06 mm Shank  $\varnothing$  D<sub>s</sub>: 12 mm  
 ISO code toolholder: AH1012K SCLCR/L06  
 Cutting point / joint: 12 mm  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CC.. 0602..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 14 mm

**Technical description**

Neck width	10 mm
Overhang L <sub>1</sub> recessed holders	38 mm
Insert size	6 mm
Centre offset L <sub>3</sub>	7 mm
suitable indexable insert	CC.. 0602..
Pack of insert screws	269028 7
Cutting point / joint	12 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	14 mm
ISO code toolholder	AH1012K SCLCR/L06
Overall length L	125 mm
Clamping height L <sub>2</sub>	11 mm
Setting angle $\kappa$	95 degrees

Shank $\varnothing D_s$	12 mm
Application type	right-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set HSS	260024