

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 12/06 mm

Order data

Order number	260022 12/06
GTIN	4045197652034
Item class	21T

Description

Boring bar HSS 12/06 mm Shank $\varnothing D_s$: 12 mm
 ISO code toolholder: AH12M SCLCR/L06
 Cutting point / joint: 12 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill $\varnothing D_{min}$: 14 mm

Technical description

suitable indexable insert	CC.. 0602..
Minimum pre-drill $\varnothing D_{min}$	14 mm
Pack of insert screws	269028 7
Insert size	6 mm
Cutting point / joint	12 mm
Centre offset L_3	7 mm
ISO code toolholder	AH12M SCLCR/L06
Overall length L	150 mm
Clamping height L_2	11 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	12 mm
Application type	right-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7