

**Garant**
**Boring bar HSS, right-hand, Shank  $\varnothing$  / insert size: 16/09 mm**

**Order data**

Order number	260022 16/09
GTIN	4045197652058
Item class	21T

**Description**

Boring bar HSS 16/09 mm Shank  $\varnothing D_s$ : 16 mm  
 ISO code toolholder: AH16Q SCLCR/L09  
 Cutting point / joint: 16 mm  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CC.. 09T3..  
 Minimum pre-drill  $\varnothing D_{min}$ : 18 mm

**Technical description**

Insert size	9 mm
Pack of insert screws	269028 8
ISO code toolholder	AH16Q SCLCR/L09
Centre offset $L_3$	11 mm
suitable indexable insert	CC.. 09T3..
Minimum pre-drill $\varnothing D_{min}$	18 mm
Cutting point / joint	16 mm
Overall length L	180 mm
Clamping height $L_2$	15 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	16 mm
Application type	right-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8