

**Garant**
**Boring bar HSS, left-hand, Shank  $\varnothing$  / insert size: 0410/03 mm**

**Order data**

Order number	260023 0410/03
GTIN	4045197652089
Item class	21T

**Description**

Boring bar HSS 0410/03 mm Shank  $\varnothing$  D<sub>s</sub>: 10 mm  
 ISO code toolholder: AH0410H SCLCR/L03  
 Cutting point / joint: 10 mm  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CC.. 0301..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 5 mm

**Technical description**

Pack of insert screws	269028 13
Centre offset L <sub>3</sub>	2.5 mm
suitable indexable insert	CC.. 0301..
ISO code toolholder	AH0410H SCLCR/L03
Minimum pre-drill $\varnothing$ D <sub>min</sub>	5 mm
Cutting point / joint	10 mm
Neck width	4 mm
Overhang L <sub>1</sub> recessed holders	24 mm
Insert size	3 mm
Overall length L	100 mm
Clamping height L <sub>2</sub>	9 mm
Setting angle $\kappa$	95 degrees

Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Set of insert screws 10 pieces	269419
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 13	269028 13