

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 0610/03 mm

Order data

Order number	260023 0610/03
GTIN	4045197652096
Item class	21T

Description

Boring bar HSS 0610/03 mm Shank \varnothing D_s: 10 mm
 ISO code toolholder: AH0610H SCLCR/L03
 Cutting point / joint: 10 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0301..
 Minimum pre-drill \varnothing D_{min}: 7 mm

Technical description

Pack of insert screws	269028 13
Overhang L ₁ recessed holders	24 mm
Neck width	6 mm
Cutting point / joint	10 mm
suitable indexable insert	CC.. 0301..
Insert size	3 mm
ISO code toolholder	AH0610H SCLCR/L03
Centre offset L ₃	2.5 mm
Minimum pre-drill \varnothing D _{min}	7 mm
Overall length L	100 mm
Clamping height L ₂	9 mm
Setting angle κ	95 degrees

Shank Ø D _s	10 mm
Application type	left-hand
Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269419
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Set of insert screws Type 13	269028 13