

**Garant**
**Boring bar HSS, left-hand, Shank  $\varnothing$  / insert size: 08/06 mm**

**Order data**

Order number	260023 08/06
GTIN	4045197652119
Item class	21T

**Description**

Boring bar HSS 08/06 mm Shank  $\varnothing D_s$ : 8 mm  
 ISO code toolholder: AH08K SCLCR/L06  
 Cutting point / joint: 8 mm  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CC.. 0602..  
 Minimum pre-drill  $\varnothing D_{min}$ : 10 mm

**Technical description**

suitable indexable insert	CC.. 0602..
Minimum pre-drill $\varnothing D_{min}$	10 mm
Insert size	6 mm
Centre offset $L_3$	5 mm
ISO code toolholder	AH08K SCLCR/L06
Cutting point / joint	8 mm
Pack of insert screws	269028 7
Overall length L	125 mm
Clamping height $L_2$	7 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	8 mm
Application type	left-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7