

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 0810/06 mm

Order data

Order number	260023 0810/06
GTIN	4045197652126
Item class	21T

Description

Boring bar HSS 0810/06 mm Shank \varnothing D_s: 10 mm
 ISO code toolholder: AH0810J SCLCR/L06
 Cutting point / joint: 10 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill \varnothing D_{min}: 12 mm

Technical description

Overhang L ₁ recessed holders	32 mm
Pack of insert screws	269028 7
Minimum pre-drill \varnothing D _{min}	12 mm
ISO code toolholder	AH0810J SCLCR/L06
Centre offset L ₃	6 mm
Cutting point / joint	10 mm
suitable indexable insert	CC.. 0602..
Insert size	6 mm
Neck width	8 mm
Overall length L	110 mm
Clamping height L ₂	9 mm
Setting angle κ	95 degrees

Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7
Boring bar set HSS	260025