

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 1012/06 mm

Order data

Order number	260023 1012/06
GTIN	4045197652140
Item class	21T

Description

Boring bar HSS 1012/06 mm Shank \varnothing D_s: 12 mm
 ISO code toolholder: AH1012K SCLCR/L06
 Cutting point / joint: 12 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill \varnothing D_{min}: 14 mm

Technical description

Centre offset L ₃	7 mm
ISO code toolholder	AH1012K SCLCR/L06
Cutting point / joint	12 mm
Insert size	6 mm
Pack of insert screws	269028 7
Neck width	10 mm
Minimum pre-drill \varnothing D _{min}	14 mm
suitable indexable insert	CC.. 0602..
Overhang L ₁ recessed holders	38 mm
Overall length L	125 mm
Clamping height L ₂	11 mm
Setting angle κ	95 degrees

Shank Ø D _s	12 mm
Application type	left-hand
Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set HSS	260025