

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 1216/06 mm

Order data

Order number	260023 1216/06
GTIN	4045197652164
Item class	21T

Description

Boring bar HSS 1216/06 mm Shank \varnothing D_s: 16 mm
 ISO code toolholder: AH1216M SCLCR/L06
 Cutting point / joint: 16 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill \varnothing D_{min}: 18 mm

Technical description

ISO code toolholder	AH1216M SCLCR/L06
Overhang L ₁ recessed holders	50 mm
Centre offset L ₃	9 mm
suitable indexable insert	CC.. 0602..
Insert size	6 mm
Neck width	12 mm
Cutting point / joint	16 mm
Pack of insert screws	269028 7
Minimum pre-drill \varnothing D _{min}	18 mm
Overall length L	150 mm
Clamping height L ₂	15 mm
Setting angle κ	95 degrees

Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set HSS	260025