

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 16/09 mm

Order data

Order number	260023 16/09
GTIN	4045197652171
Item class	21T

Description

Boring bar HSS 16/09 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: AH16Q SCLCR/L09
 Cutting point / joint: 16 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 09T3..
 Minimum pre-drill $\varnothing D_{min}$: 18 mm

Technical description

Pack of insert screws	269028 8
Centre offset L_3	11 mm
ISO code toolholder	AH16Q SCLCR/L09
Minimum pre-drill $\varnothing D_{min}$	18 mm
suitable indexable insert	CC.. 09T3..
Insert size	9 mm
Cutting point / joint	16 mm
Overall length L	180 mm
Clamping height L_2	15 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8