

Garant
Boring bar set HSS, left-hand

Order data

Order number	260025
GTIN	4045197652218
Item class	29W

Description

Boring bar set HSS ISO code toolholder: AH1012K SCLCR/L06
 ISO code toolholder: AH0608H SCLCR/L06
 ISO code toolholder: AH0810J SCLCR/L06
 ISO code toolholder: AH1216M SCLCR/L06
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill $\varnothing D_{\min}$: 8 mm

Technical description

ISO code toolholder	AH1012K SCLCR/L06
ISO code toolholder	AH0608H SCLCR/L06
ISO code toolholder	AH0810J SCLCR/L06
ISO code toolholder	AH1216M SCLCR/L06
suitable indexable insert	CC.. 0602..
Pack of insert screws	269028 7
Clamping height L_2	7 mm
Clamping height L_2	9 mm
Clamping height L_2	11 mm

Clamping height L_2	15 mm
Minimum pre-drill $\varnothing D_{\min}$	8 mm
Minimum pre-drill $\varnothing D_{\min}$	12 mm
Minimum pre-drill $\varnothing D_{\min}$	14 mm
Minimum pre-drill $\varnothing D_{\min}$	18 mm
Centre offset L_3	4 mm
Centre offset L_3	6 mm
Centre offset L_3	7 mm
Centre offset L_3	9 mm
Neck width	6 mm
Neck width	8 mm
Neck width	10 mm
Neck width	12 mm
Overall length L	100 mm
Overall length L	110 mm
Overall length L	125 mm
Overall length L	150 mm
Overhang L_1 recessed holders	25 mm
Overhang L_1 recessed holders	32 mm
Overhang L_1 recessed holders	38 mm
Overhang L_1 recessed holders	50 mm
Application type	left-hand
Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7