



Boring bar steel, right-hand, Shank Ø / insert size: 10/06 mm



Order data

Order number	260028 10/06
GTIN	4960664541157
Item class	25U

Description

Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank Ø D_s : 10 mm

ISO code toolholder: A10L SCLCR/L06

Setting angle κ : 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill Ø D_{min} : 12 mm

Centre offset L_3 : 6 mm

Technical description

Centre offset L_3	6 mm
Insert screw	269022 2
suitable indexable insert	CC.. 0602..
ISO code toolholder	A10L SCLCR/L06
Minimum pre-drill Ø D_{min}	12 mm
Insert size	6 mm
Overall length L	140 mm
Clamping height L_2	9 mm
Setting angle κ	95 degrees
Shank Ø D_s	10 mm

Application type	right-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Clamping screw	269405
Clamping screw Type 2	269022 2
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8