


Garant
Boring bar steel, right-hand, Shank Ø / insert size: 10/06 mm

Order data

Order number	260032 10/06
GTIN	4045197652232
Item class	21T

Description

Boring bar steel 10/06 mm Shank Ø D_s: 10 mm

ISO code toolholder: A10K SCLCR/L06

Setting angle κ: 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill Ø D_{min}: 12 mm

Centre offset L₃: 7 mm

Technical description

ISO code toolholder	A10K SCLCR/L06
Insert size	6 mm
Centre offset L ₃	7 mm
suitable indexable insert	CC.. 0602..
Pack of insert screws	269028 22
Minimum pre-drill Ø D _{min}	12 mm
Overall length L	125 mm
Clamping height L ₂	9 mm
Setting angle κ	95 degrees
Shank Ø D _s	10 mm
Application type	right-hand
Boring depth up to	3×D

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 22	269028 22
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269440