


Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 12/06 mm

Order data

Order number	260032 12/06
GTIN	4045197652249
Item class	21T

Description

Boring bar steel 12/06 mm Shank $\varnothing D_s$: 12 mm

ISO code toolholder: A12L SCLCR/L06

Setting angle κ : 95 degrees

suitable indexable insert: CC.. 0602..

Minimum pre-drill $\varnothing D_{min}$: 16 mm

Centre offset L_3 : 9 mm

Technical description

ISO code toolholder	A12L SCLCR/L06
Minimum pre-drill $\varnothing D_{min}$	16 mm
Pack of insert screws	269028 22
Centre offset L_3	9 mm
Insert size	6 mm
suitable indexable insert	CC.. 0602..
Overall length L	140 mm
Clamping height L_2	11 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	12 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 22	269028 22
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269440