

**Garant**
**Boring bar steel, right-hand, Shank Ø / insert size: 16/09 mm**

**Order data**

Order number	260032 16/09
GTIN	4045197652256
Item class	21T

**Description**

Boring bar steel 16/09 mm Shank Ø  $D_s$ : 16 mm  
 ISO code toolholder: A16Q SCLCR/L09  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CC.. 09T3..  
 Minimum pre-drill Ø  $D_{min}$ : 20 mm  
 Centre offset  $L_3$ : 11 mm

**Technical description**

suitable indexable insert	CC.. 09T3..
Insert size	9 mm
ISO code toolholder	A16Q SCLCR/L09
Minimum pre-drill Ø $D_{min}$	20 mm
Centre offset $L_3$	11 mm
Pack of insert screws	269028 14
Overall length L	180 mm
Clamping height $L_2$	14 mm
Setting angle $\kappa$	95 degrees
Shank Ø $D_s$	16 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269420
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 14	269028 14