


Garant
Boring bar steel, right-hand, Shank Ø / insert size: 20/09 mm

Order data

Order number	260032 20/09
GTIN	4045197652263
Item class	21T

Description

Boring bar steel 20/09 mm Shank Ø D_s : 20 mm

ISO code toolholder: A20R SCLCR/L09

Setting angle κ : 95 degrees

suitable indexable insert: CC.. 09T3..

Minimum pre-drill Ø D_{min} : 25 mm

Centre offset L_3 : 13 mm

Technical description

ISO code toolholder	A20R SCLCR/L09
Insert size	9 mm
suitable indexable insert	CC.. 09T3..
Pack of insert screws	269028 14
Minimum pre-drill Ø D_{min}	25 mm
Centre offset L_3	13 mm
Overall length L	200 mm
Clamping height L_2	18 mm
Setting angle κ	95 degrees
Shank Ø D_s	20 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269420
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 14	269028 14