


Garant
Boring bar steel, right-hand, Shank Ø / insert size: 40/12 mm

Order data

Order number	260032 40/12
GTIN	4045197652294
Item class	21T

Description

Boring bar steel 40/12 mm Shank Ø D_s: 40 mm

ISO code toolholder: A40T SCLCR/L12

Setting angle κ: 95 degrees

suitable indexable insert: CC.. 1204..

Minimum pre-drill Ø D_{min}: 49 mm

Centre offset L₃: 27 mm

Technical description

Shim	269005 6
suitable indexable insert	CC.. 1204..
Minimum pre-drill Ø D _{min}	49 mm
ISO code toolholder	A40T SCLCR/L12
Centre offset L ₃	27 mm
Pack of insert screws	269028 20
Shim screw	269013 5
Insert size	12 mm
Overall length L	300 mm
Clamping height L ₂	38.5 mm
Setting angle κ	95 degrees
Shank Ø D _s	40 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim Type 6	269005 6
Shim screw Type 5	269013 5
Shim screw	269210
Shim	269030
Set of insert screws Type 20	269028 20
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269430